

The Float Pro® control switch is a narrow angle or wide angle control switch that is used to monitor liquid levels in wastewater and sewage applications. The Float Pro® series allows for a multitude of different float styles and functions.

Float Pro® Control Switches

Float Pro® Series Control Switches/Floats - Normally Open - Narrow Angle			
Model	Туре	Cord Length	Angle
FPC0N20**	Normally Open	20'	Narrow
FPC0N30	Normally Open	30'	Narrow
FPC0N50	Normally Open	50'	Narrow
FPC0N100	Normally Open	100'	Narrow

Note: FPC0N20** N/O Narrow Angle Float Switch is standard on WS Series®, Knight Series®, Hydra®, Parabola®, and Trident® control products.

Float Pro® Series Control Switches/Floats - Normally Open - Wide **Angle**

Model	Туре	Cord Length	Angle
FPC0W20	Normally Open	20'	Wide
FPC0W30	Normally Open	30'	Wide
FPC0W50	Normally Open	50'	Wide
FPC0W100	Normally Open	100'	Wide

Float Pro® Series Control Switches/Floats - Normally Closed -**Narrow Angle**

<u> </u>			
Model	Туре	Cord Length	Angle
FPC1N20	Normally Closed	20'	Narrow
FPC1N30	Normally Closed	30'	Narrow
FPC1N50	Normally Closed	50'	Narrow
FPC1N100	Normally Closed	100'	Narrow

Float Pro® Series Control Switches/Floats - Normally Closed -Wide Angle

Model	Туре	Cord Length	Angle
FPC1W20	Normally Closed	20'	Wide
FPC1W30	Normally Closed	30'	Wide
FPC1W50	Normally Closed	50'	Wide
FPC1W100	Normally Closed	100'	Wide



Call us toll-free at 888.733.9283 to speak with one of our expert Sales Engineers.

Technical Specifications

Parameter	Rating	
Electrical Requirements	5 amps; 125VAC/250VAC, 50/60 Hz	
Cable Type	Flexible 18 gauge; 2 conductor (UL, CSA) SJOW	
Float Description	2 7/8" diameter, 4 1/2" long, high impact, corrosion-resistant, polypropylene housing for use in sewage and water up to 140°F (60°C)	
Max. Water Depth	30' (9 meters), 13 PSI (90 kPa)	





951.487.8073 / 888.733.9283

www.seewaterinc.com

sales@seewaterinc.com











Float Pro® Control Switch











